



OG-100 Solar Thermal Collector Certification

No./10002165

Issued: July 07, 2023

Expiration Date: February 01, 2024

www.solar-rating.org | (800) 423-6587 | (562) 699-0543

CERTIFICATION HOLDER: DualSun 2 rue Marc Donadille 13013 Marseille France www.dualsun.fr	EVALUATION SUBJECT	
	BRAND:	SPRING
	MODEL:	DSTI425M12-B320SBB7
	TYPE:	Photovoltaic-Thermal Hybrid Collector (PVT), Unglazed, Integrated

PRODUCT CERTIFICATION SYSTEM:

The ICC-SRCC OG-100 certification program includes evaluation and performance ratings for solar thermal collectors as established in the [ICC-SRCC Rules for Solar Heating & Cooling Product Listing Reports](#). The program also includes periodic factory inspections and surveillance of the manufacturer's quality management system.

COMPLIANCE WITH THE FOLLOWING STANDARD(S): [ICC 901/SRCC 100 - 2020, Solar Thermal Collectors Standard](#)

OG-100 THERMAL PERFORMANCE RATINGS:

ICC-SRCC OG-100 thermal performance ratings provided for the collector are calculated for a 24-hour period using OG-100 standard conditions using collector parameters measured through laboratory testing. Actual performance will vary with local conditions, installation details and usage.

COLLECTOR SPECIFICATIONS:

The certified collector has the following specifications and ratings based on testing to the standards above.

PEAK THERMAL POWER RATING ¹		Gross Area	2.08 m ² (22.4 ft ²)
792 W		Length	1.90 m (6.2 ft)
		Width	1.10 m (1.2 ft)
		Empty Weight	29.7 kg (65.5 lb)
Tested PV Module Specifications² (@STC): P_{MPP} : 425 W I_{SC} : 12.56 ADC V_{OC} : 43.40 VDC		Fluid Capacity	5.0 L (1.3 gal)
		Max Design Pressure	150 kPa (22 psi)
		Approved Fluids	Water, Chlorinated Water

1: Peak thermal power production at Standard Rating Condition (SRC) and Blue Sky conditions as defined in ISO 9806. See Power Output Section for more information and conditions.

2: Photovoltaic electrical power production not included in published OG-100 or ISO 9806 performance ratings.

OG-100 THERMAL PERFORMANCE RATINGS:

ICC-SRCC OG-100 thermal performance ratings are provided for one collector are calculated for a 24-hour period using OG-100 standard conditions based on collector performance parameters measured through laboratory testing. Results are provided for two use categories (A and B), under three levels of solar irradiance (high, medium, low). Actual performance will vary with local conditions, installation details and usage. Results do not include electrical energy production from photovoltaic cells.

APPLICATION*	OG-100 CATEGORY	OG-100 DAILY THERMAL ENERGY OUTPUT (kWh/d)		
		HIGH (6.3 kWh/m ² ·d)	MEDIUM (4.7 kWh/m ² ·d)	LOW (3.1 kWh/m ² ·d)
Pool Heating in Warm Climate (T _r -T _a = -5°C)	A	5.7	4.5	3.4
Pool Heating in Cool Climate (T _r -T _a = +5°C)	B	3.1	2.0	0.9

* T_r: Inlet Water Temperature to Collector, T_a: Ambient Air Temperature

THERMAL EFFICIENCY:

The efficiency of solar thermal collectors is determined using test methods set in ICC 901/SRCC 100, based on ISO 9806 procedures. Results are processed to provide unique coefficients for efficiency equations, provided in several forms below. For the simplified equations, instantaneous power at normal incidence is given by $\dot{Q} = \eta_{hem} A_G G$. Incident Angle Modifiers (IAMs) are also provided to indicate the change in output as the angle of solar irradiance changes on the collector plane.

T _m : Average temperature of the fluid within the collector (between the inlet and outlet). T _a : Temperature of the ambient air around the collector. G: Hemispherical solar irradiance. Comprised of beam (b) and diffuse (d). E _L : Longwave (infrared) irradiance. ε/α: Collector emissivity/absorptance ratio.	RATING CONDITIONS	
	Gross Collector Area (A _G)	2.081 m ²
	Fluid Mass Flowrate (\dot{m})	0.020 kg/(m ² s)
	Test Fluid	Water
	Performance Test Standard	ISO 9806-2017

GENERAL THERMAL PERFORMANCE EQUATION (ISO 9806-2017, T_m, A_G)


Extended Thermal Efficiency Equation*

$$\dot{Q} = A_G(\eta_{0,b}K_b(\theta_L, \theta_r)G_b + \eta_{0,b}K_dG_d - a_1(T_m - T_a) - a_2(T_m - T_a)^2 - a_3u'(T_m - T_a) + a_4(E_L - \sigma T_a^4) - a_5\left(\frac{dT_m}{dt}\right) - a_6u'G - a_7u'(E_L - \sigma T_a^4) - a_8(T_m - T_a)^4)$$

	η _{0,b}	K _d	a ₁	a ₂	a ₃	a ₄	a ₅	a ₆	a ₇	a ₈
VALUE	0.355	1.000	12.740	0.000	1.106	0.000	16219	0.016	0.000	0.000
UNITS	-	-	W/(m ² K)	W/(m ² K ²)	J/(m ³ K)	-	J/(m ² K)	s/m	W/(m ² K ⁴)	W/(m ² K ⁴)


* General thermal efficiency equation for mean (T_m) fluid temperature provided in accordance with ISO 9806-2017. Where data measured using a standard other than ISO 9806-2017, additional assumptions may be applied to determine extended equation coefficients. Reduced surrounding air speed (u') is defined as u'=u-3 m/s. See ISO 9806-2017 for other coefficient definitions.

DIRECT INCIDENT ANGLE MODIFIERS (IAM)



POWER OUTPUT:

The instantaneous power output of the collector under different conditions is calculated at the Standard Reporting Conditions (SRC) defined by ISO 9806-2017 using the measured performance coefficients above.



STANDARD COLLECTOR POWER OUTPUT (W) – THERMAL ONLY

Based on Standard Rating Conditions (SRC) and mean temperature (T_m) in accordance with ISO 9806-2017

$T_m - T_a$ (°C)	Blue sky $G_b = 850, G_d = 150$ (W/m ²)	Hazy sky $G_b = 440, G_d = 260$ (W/m ²)	Grey sky $G_b = 0, G_d = 400$ (W/m ²)
-10	1019	782	544
0	792*	555	317
10	565	328	90
20	339	101	0
30	112	0	0
40	0	0	0
50	0	0	0
60	0	0	0

* Peak thermal power is defined by ISO 9806 as the Blue Sky irradiance conditions at $T_m - T_a = 0$ and normal incidence, as defined in ISO 9806.

IDENTIFICATION:

Certified systems must be identified with the OG-300 certification mark below in accordance with the [Rules for Certification Mark and Certificate Use](#) and labeled in with the information below per ICC 901/SRCC 100:



1. Manufacturer's name and model number.
2. OG-100 collector certification number
3. Maximum operating pressure
4. Dry weight
5. Fluid volume
6. Compatible heat transfer fluids
7. Standard stagnation temperature
8. Year of manufacture and/or serial number.

CONDITIONS:

1. Collector must be installed and operated in accordance with the solar thermal and PV manufacturer's published instructions and local codes and regulations. Solar thermal panel must be assembled with the photovoltaic module in accordance with the solar thermal manufacturer's installation requirements.
2. OG-100 Standard Performance Ratings and Standard Collector Power Output have been calculated for the tested components using standardized conditions established by the OG-100 program and associated test standards. OG-100 performance ratings and power output values do not include electrical power production for PVTs. Actual performance will vary based on the specific usage, installation and local environmental conditions. Performance ratings will differ if a qualifying PV module is substituted.
3. The collector listed in this ICC-SRCC OG-100 certification must be labeled in accordance with the [ICC-SRCC Rules for Mark and Certificate Use](#).
4. OG-100 certifications do not include mounting hardware and fixtures.
5. Solar thermal collectors and mounting hardware and appurtenances must comply with all applicable local requirements for fire resistance. Solar thermal collectors must be mounted in accordance with the requirements of the collector and mounting hardware manufacturers to comply with local codes for structural loading for wind, seismic, snow and other loads.
6. Solar thermal collectors must be used with the heat transfer fluids listed in this document.
7. All electrical wiring, connections, components and labeling shall comply with the National Electrical Code (NFPA 70) and other local regulations and as specified by the manufacturer. OG-100 certification does not address electrical safety and durability. Separate photovoltaic listing to UL 1703 or UL 61730 is required for the installed PV module.
8. Solar thermal collector manufactured under a quality control program subject to periodic evaluation in accordance with the requirements of ICC-SRCC.
9. This document must be reproduced in its entirety.
10. Certification status should be confirmed on the ICC-SRCC Directory at www.solar-rating.org

Shawn Martin

Vice President of Technical Services, ICC-SRCC

